

SAFETY DATA SHEET

Mitsubishi Chemical Advanced Materials 2120 Fairmont Avenue Reading, PA, 19609 T: 610-320-6600 Regulatorysupport.mcam@mcgc.com mcam.com

ID# SDS-1704 Issue Date: June 1, 2015 Revised Date: October 28, 2024 Revision No. 003

Section 1: Identification

Product Identifier: Altron[™] PPO

Manufacturer:

Mitsubishi Chemical Advanced Materials, Inc. 2120 Fairmont Ave. Reading, PA 19605 (610) 320-6600

In case of an emergency, please call Chemtrec 1-800-424-9300.

Recommended Use: Engineering thermoplastic stock shape

Section 2: Hazard Identification

GHS – Classifications

Classification: None

Signal Word: None

Pictograms and Symbols: None

Hazard Statements: None

Precautionary Statements: None

Section 3: Composition/Information on Ingredients

This is a polymeric material. All constituents are encapsulated within the polymer system and therefore unlikely to result in exposure under normal conditions of processing and handling.

Chemical Name	CAS No.	Weight %
Polyphenylene Ether	25134-01-4	>90
Phosphoric acid, triphenyl ester	115-86-6	1-5
Carbon Black	1333-86-4	0.1-1.0

Section 4: First-Aid Measures

Eyes: Flush with plenty of water for at least 15 minutes. Seek medical attention if irritation continues.

Skin: No health risks concerning skin contact at room temperature. Wash with soap and water. If molten material comes in contact with the skin, cool under running water. Do not attempt to remove the molten material from the skin. Get medical attention immediately.



Inhalation: If fumes from overheating are inhaled, remove to fresh air. Seek medical attention if respiratory symptoms occur or breathing becomes difficult.

Ingestion: Rinse the victim's mouth with plenty of water. Do not induce vomiting. Seek medical attention.

Section 5: Fire-Fighting Measures

Fire-fighters should protect themselves from decomposition and combustion products by using a fullface self-contained breathing apparatus and impervious protective clothing. Extinguish fires with water spray and foam. Carbon dioxide and dry chemical media are not recommended because their lack of cooling capacity may permit re-ignition.

Hazardous gases/vapors produced in fire are: carbon oxides and Hydrocarbon fragments.

Dust is flammable and explosive when finely divided and suspended in air.

Section 6: Accidental Release Measures

If a spill occurs, stop the leak at the source and sweep up for disposal. Do not flush to sewers or waterways.

Section 7: Handling and Storage

Precautions for Safe Handling

Personal hygiene such as washing the hands and face immediately after working with this material and before eating is recommended.

Dust may form explosive mixtures with air. Avoid dust formation and control ignition sources. Plastic dust particles suspended in air are combustible and may be explosive. Keep away from heat, sparks, flame, and other ignition sources. Prevent dust accumulations and dust clouds. Employ ground, bonding, venting, and explosive relief provisions in accordance with accepted engineering practices and NFPA provisions in any process capable of generating dust and/or static electricity. Explosion hazards apply only to dusts, not granular forms of this product.

The handling of powder in both loading and unloading operations, as well as fabrication, may cause dust to be formed and necessary precautions for personal protection should be used. As with all finely divided materials precautions should be taken to avoid inhalation and eye contact.

If in dust form, transfer from storage with a minimum amount of dusting. Ground all transfer, blending, and dust collecting equipment to prevent static sparks in accordance with NFPA 70 "National Electric Code." Review and comply with all relevant NFPA provisions, including but not limited to NFPA 484 and NFPA 654 related to combustible dust hazards. Remove all ignition sources from material handling, transfer, and processing areas where dust may be present. Local exhaust ventilation should be provided in work area.

Precautions for Safe Storage

Store in a sprinkler protected warehouse. Since products are organic, they will burn with a hot flame if ignited. Avoid contact with ignition sources such as open flames. Keep a fire extinguisher near if welding is done in the area of organic products. If a heat source is present, keep the area well ventilated.



Section 8: Exposure Controls/Personal Protection

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH REL
Particulates	10 mg/m ³	15 mg/m ³ – Total 5 mg/m ³ – Respirable	Not Determined
Phosphoric Acid, Triphenyl Ester	3.5 mg/m ³	3.5 mg/m ³	Not Determined
Carbon Black	3.5 mg/m ³	3.5 mg/m ³	3.5 mg/m ³

Engineering Measures:

Provide local exhaust ventilation to keep airborne particulate concentrations below 15 mg/m³, the OSHA limit for nuisance dusts.

Personal Protective Equipment: Eyes/Face

Safety glasses with side shields.

Personal Protective Equipment: Skin

When handling molten material, protective clothing such as long sleeves or laboratory coat should be worn. Use heat-resistant gloves, boots, and face protection.

Personal Protective Equipment: Respiratory

If levels are above published OELs, then a NIOSH approved respirator.

Good industrial hygiene practice should be followed which includes preventing eye contact, minimizing skin contact, and minimizing inhalation of dust, vapors or mist.

Section 9: Physical and Chemical Properties

Appearance and Odor Odor Threshold Specific Gravity (Relative Density) Solubility in Water VOC Content (%) pH Melting Point/Freezing Point

Vapor Pressure Vapor Density Evaporation Rate Boiling Point Flammability Flash Point Explosion Data

Auto ignition Point Partition Coefficient: n-octanol/water Decomposition Temperature Viscosity

Solid in rod, plate, or bushing form with no odor No Information Available >1 Insoluble Negligible No data available This product does not exhibit a sharp melting point but softens gradually over a wide temperature range. No data available No data available No data available No data available Combustible No data available LEL – No data available UEL - No data available 914°F (Estimated) No data available No data available No data available

3/7



Section 10: Stability and Reactivity

Reactivity:

None known

Chemical Stability:

Material is stable under normal industrial conditions and is not susceptible to hazardous polymerization.

Conditions to Avoid:

To avoid thermal decomposition, avoid elevated temperatures. Heating can result in the formation of gaseous decomposition products, some of which may be hazardous.

Incompatibility:

None known

Hazardous Decomposition Products:

At elevated temperatures trace levels of alkylphenols, aldehydes and alcohols, aliphatic amines, dimethylcyclohexanone, trimethylanisole, dihydrobenzofuran, styrene, 4-vinylcyclohexene, phenols, triarylphosphate esters, cyclopentanone, carbon dioxide, carbon monoxide will occur.

Section 11: Toxicological Information

Signs and Symptoms of Overexposure: Eye irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blurred vision. Skin irritation signs and symptoms may include a burning sensation, redness and swelling. Respiratory irritation signs and symptoms may include a temporary burning sensation of the nose and throat, coughing, and/or difficulty breathing.

Aggravated Medical: None.

Acute Effects: Non-toxic. Skin Corrosion/Irritation: Not irritating to the skin. Serious Eye Damage/Irritation: Particulates can be mechanically irritating to the eyes. Ingestion: None. Inhalation: Inhalation of particulates may produce respiratory tract irritation. Respiratory or Skin Sensitization: Not expected to be a sensitizer.

Subchronic Effects: No data available

Chronic Effects:

Germ Cell Mutagenicity: Not expected to be a germ cell mutagen.

Carcinogenicity: Not classifiable as carcinogen to humans (group 3 IARC). OSHA, IARC and/or NTP have listed carbon black as a carcinogen. This colorant is essentially bound to the plastic matrix and are unlikely to contribute to workplace exposure under recommended processing conditions.

Reproductive Toxicity: There aren't known reproductive toxicity effects.

STOT-single Exposure: At dust form, may cause respiratory irritation with cough and sneezing. **STOT –multiple Exposure:** There aren't known repeated exposure effects.

Aspiration Hazard: No data available. Not expected to be an aspiration hazard.



Primary Route of Entry: Inhalation of particulates.

Section 12: Ecological Information

Ecotoxicity:

There aren't known ecological toxicity values.

Persistence and degradability:

It's expected high persistence and slow degradability.

Bioaccumulative Potential:

It's expected moderate to high bioaccumulative potential.

Mobility in Soil:

No data available

Other Adverse Effects:

No data available

Chemical Name	Toxicity to Algae	Toxicity to Fish	Microtox	Daphnia Magna (Water Flea)

Section 13: Disposal Considerations

According to the 'European Waste Catalogue and Hazardous Waste List', uncontaminated waste from the products is not classified as hazardous. The following six-digit codes can be used:

	07 02 13	waste plastic from the manufacture, formulation, supply and use of plastics
	12 01 05	plastic shavings and turnings
	16 01 19	plastic, from end-of-life vehicles from different means of transport (including off-road machinery) and wastes from dismantling of end-of-life vehicles and vehicle maintenance
	17 02 03	plastic construction and demolition wastes
	20 01 39	plastics from municipal wastes (household waste and similar commercial, industrial and institutional wastes)
Waste disposal:	landfill car	ycling is not feasible, waste disposal by incineration or be applied. Disposal methods shall conform to local or ernment regulations.

Section 14: Transportation Information

US Department of Transportation Classification (49CFR)

Not classified as hazardous for transport.



Section 15: Regulatory Information

SARA Section 302 & 304: No chemicals

SARA Section 313:

The following component is subject to reporting levels established by SARA Title III, Section 313:

None

TSCA: All components of this product are either listed or are exempt on the TSCA inventory.

Section 16: Other Information

Label Information

Product Identifier: Altron[™] PPO

Manufacturer:

Mitsubishi Chemical Advanced Materials, Inc. 2120 Fairmont Ave. Reading, PA 19605 (610) 320-6600

In case of an emergency, please call Chemtrec 1-800-424-9300.

Classification: None

Signal Word: None

Pictograms and Symbols: None

Hazard Statements: None

Precautionary Statements: None

The information set forth herein has been gathered from standard reference materials and/or supplier test data and is, to the best knowledge and belief of Mitsubishi Chemical Advanced Materials, Inc., accurate and reliable. Such information is offered solely for your consideration, investigation and verification, and it is not suggested or guaranteed that the hazard precautions or procedures mentioned are the only ones that exist. Mitsubishi Chemical Advanced Materials, Inc., makes no warranties, expressed or implied, with respect to the use of such information or the use of the specific material identified herein in combination with any other material or process, and assumes no responsibility therefor.



Acetron[™], Altron[™], Armor-X[™], BIOpreg[™], Borotron[™], carboNXT[™], Ceram P[™], Cestidur[™], Chirulen[™], Duratron[™], Ertacetal[™], Ertalon[™], Ertalyte[™], Extrulen[™], Flextron[™], Fluorosint[™], Ketron[™], Keylon[™], Kyron[™], KyronMAX[™], KyronTEX[™], MC[™], Nylamid[™], Nylatrack[™], Nylatron[™], Proteus[™], Quadrant[™], QuickSilver[™], RCH[™], Sanalite[™], Semitron[™], Statera[™], Sterra[™], Sultron[™], System TIVAR[™], Techtron[™], TIVAR[™], and Ultraslide[™] are registered trademarks of the Mitsubishi Chemical Advanced Materials group of companies.

All statements, technical information, recommendations, and advice are for informational purposes only and are not intended and should not be construed as a warranty of any type or term of sale. The reader, however, is cautioned that Mitsubishi Chemical Advanced Materials does not guarantee the accuracy or completeness of this information and it is the customer's responsibility to test and assess the suitability of the products of Mitsubishi Chemical Advanced Materials in any given application or for use in a finished device.